



MULTI-METAL COATING

LEARN MORE AT WWW.FERTAN-USA.COM

PRODUCT HIGHLIGHTS

- Outstanding and unique bonding ability to steel, aluminum, and copper
- Extremely resistant
- Comparable to hot dip galvanized



FERTAN® MULTI-METAL COATING providing long-term corrosion protection by creating a high grade surface finish that is oil resistant. FERTAN MULTI-METAL COATING has an outstanding and unique bonding ability with steel, aluminum, and copper, and offers excellent adhesion with commercial lacquers and paints.

DIFFERENTIATORS

- Can be used as a final coating/treatment
- Long-term option
- Temperature resistant up to 572°F

Safety Precaution: In case of contact with skin, wash with plenty of running water.

APPLICATION INSTRUCTIONS

1. Make sure the surface area is rust and grease free. If rust needs to be removed or converted we recommend FERTAN RUST REMOVER or FERTAN RUST CONVERTER.
2. Shake FERTAN MULTI-METAL COATING for at least 3 minutes prior to application.
3. Spray FERTAN MULTI-METAL COATING in 1 thin coat, holding nozzle 6–10 inches (15–25 cm) from surface.
4. Allow 1 hour to dry.
**Completely cured after 2-3 days at 68°F (20°C).*
5. Painting optional.