

CLESSINOX

STAINLESS STEEL

High pressure cylinder hose DN10 PN30

Metallic flexible hose: Armoured and designed for high pressure, meeting requirements of manufacturing standards BS EN ISO 10380 and an ideal replacement for rubber.



- 🔥 Rodent resistant
- 🔥 Ultraset – new improved excess flow system
- 🔥 UV stabilised outer cover
- 🔥 Improved durability over rubber
- 🔥 Wide bore design with reduced pressure loss
- 🔥 Exceeds standard pull test requirements
- 🔥 Highly flexible
- 🔥 Traceable manufacturing
- 🔥 No internal rubber components
- 🔥 Plasticiser free
- 🔥 Cost effective
- 🔥 Easily recyclable & environmentally friendly

The wide bore design and Ultraset non-return valves, provide silent operation and fast reset, having no plasticiser material in contact with LPG helping to minimise oil contamination in downstream equipment. Armoured with additional braiding and coated with UV stabilised PVC outer sleeve, this hose is designed and constructed for use with LPG cylinders in accordance to BS6891, BS5482 and UKLPG CoP24.

Markings on Hose

DN - Nominal inside bore diameter
PN - maximum operating pressure in bar
MM/20XX - Date of manufacture

Clessinox high pressure hoses are rated 5kgH/70kwh, providing low pressure loss and full capacity even at cylinder pressures as low as 0.5bar, ensuring effective LPG cylinder usage.

Service life – Clesse recommends replacement at 10 years, however if there are no signs of visible deterioration, damage to hose or leakage at the connections and along its length, then lifespan can be extended*. Clesse recommends that the hose is inspected regularly and at cylinder exchange.

**if service and environmental conditions allow.*

Use the clear line on the PVC outer sheath to ensure the product is not subjected to twisting or torsional forces. Torque can occur upon installation or when the hose is in use. Never support weight from the hose, or bend further than the minimum bend radius of 50mm.

Contact your Clesse distributor for more details on changeover kit prices with stainless steel hoses

Clearly printed hose with identification markings

Manufacturer Brand Name

Suitable for use with

International Standard

CLESINOX STAINLESS STEEL - LPG - P.MAX 30 BAR - BS EN ISO 10390 - MTC 03/2017

Material

P = Max Operating Pressure

Manufacturing Date

Product Codes And Descriptions

Part code	Description
UUSST500MMNRV	20" Clessinox Stainless Steel Pigtail inc. Ultraset NRVEXF UKPOL x M20 Female Swivel
UUSST750MMNRV	33" Clessinox Stainless Steel Pigtail inc. Ultraset NRVEXF UKPOL x M20 Female Swivel
UUSST500MMST	20" Clessinox Stainless Steel Pigtail Straight Through UKPOL x M20 Female Swivel
UUSST500MMPXP	20" Clessinox Stainless Steel Pigtail UKPOL x UKPOL Straight Through
UUSST750MMPXP	33" Clessinox Stainless Steel Pigtail UKPOL x UKPOL Straight Through
UUSST1000MMNRV	1mtr Clessinox Stainless Steel Pigtail inc. Ultraset NRVEXF UKPOL x M20 Female Swivel



CLESINOX
STAINLESS STEEL

Available as a replacement to rubber pigtails from your Clesse distributor NOW