





















RECO SPACE DATA SHEET

	PANEL TYPE	RECO SPACE	100% PVC
	PANEL SIZE	2440 x 1220 x 2mm	Half panel 2440 x 610 x 2mm
	WEIGHT	9kg	Half Panel 4.5kg (3kg per m ²)
	FINISH	SATIN	Plain White available without printed finish
	COLOURS	White	See design ranges
	SCRATCH RESITANCE	PVC Hard Coat	Excellent Resistance±
	WATER RESITANCE	Non porous	100% Waterproof
	CHEMICAL RSISTANCE	UPVC Hard Coat	Excellent Resistance°
	SLIP RESITANCE	Excellent	Suitable for some floors^ DIN 51130. R 10
	CLEANING	Easy clean Mould resistant	No need for abrasive cleaning
	CUTTING	Jigsaw or Fine-toothed saw	Easy to cut

	FIXING	HG Adhesive	No profiles
	DENSITY ISO 1183	D-792	1.40 – 1.54 g/cm ³
	IMPACT STRENGTH ISO 179/fa	CHARPY at 23°C	9 KJ/m ²
	SOFTENING TEMP ISO 306A	VICAT D-1525-B	72°C
	FLAME RESITANCE	BS476 Part 7	Class 2*
	UV RESISTANCE	Anti UV Coating	Good
	RECYCLABLE	100% RECYCLABLE	Panels can be returned to us for specialist recycling

KEY FEATURES - Advantages over Ceramic Tiles

- 20% more insulation
- No strip out. Fit over existing Tiles or other sound surface
- 100% recyclable. No landfill
- 100% waterproof
- No waterproof tanking materials required
- No grout - No Mould or maintenance
- 1/3rd the fitting time
- No skilled labour required
- Low Carbon footprint
- Cost savings to Installer

º Resistant to a wide range of chemicals. Specific details on request.

± PVC Hard Coat – Gives excellent scuff, scratch and graffiti resistance. Data available on request.

* When adhered to plasterboard or equivalent FR material and fitted per Reco instructions. Suitable for all areas except emergency exits. Splashbacks. When fitting allow a minimum of 60 mm between the rear edge of the hob. With naked flame gas hobs allow a minimum of 100 mm and fit clear heat resistant glass in front of the panel, the width of the hob.

^Contact us for more info in regard to wet floors.

CARE INSTRUCTIONS AND GUARANTEE

Reco Space panels are guaranteed against faulty materials or manufacture for a period of 10 years when installed and maintained in accordance with our manufacturer's instructions. Download full instructions for Reco Space.

RECO SPACE and RECO SEAL SYSTEM™

Panel Joins - The panel edges match up and combined with sealant create an almost seamless appearance.

Flat seam - No surface profiles. Avoids trapped dirt and germs.

Double Seal -Watertight joins' supported by internal and external corners that can be easily and perfectly aligned, without scribing, using Reco Backing strips if required.

Line Bending -Reco Space is ideal for line bending using professional equipment. This avoids corner joints and can assist the optimum use of material.

Easy replacement and recycling

All Reco panels are designed to be easily replaced and recycled at the end of their life. Correctly installed panels can be removed without damage to the surface behind and a new panel fitted.

Installation offcuts can be returned to Reco Surfaces Ltd, Enterprise House, Freiston, Boston, Lincs PE22 0JZ.

100% recyclable

Replaced panels which have been installed in accordance with the Reco Seal System can be recycled if returned to Reco.

*Patents pending.

