

SECTION 1: Identification of the	ne substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	Ring Free XHD 30
Product number	7423
Internal identification	GHS21570
REACH registration number	n/a Mixture
1.2. Relevant identified uses o	f the substance or mixture and uses advised against
Identified uses	Engine oil.
Uses advised against	Non specified unless otherwise stated within this MSDS
1.3. Details of the supplier of the supplier of the supplier of the supplier of the supplication of the su	ne safety data sheet
Supplier	Morris Lubricants
	Castle Foregate
	Shrewsbury SY1 2EL
	08.45 - 17.00 GMT
	T: (+44)(0)1743 232200
	F: (+44)(0)1743 353584 sds@morris-lubricants.co.uk
1.4. Emergency telephone nur	
Emergency telephone	+44 (0)1743 232200 (08.45 - 17.00 hrs GMT)
SECTION 2: Hazards identifica	ation
2.1. Classification of the substa	ance or mixture
Classification	
Physical hazards	Not Classified
Health hazards	Elicitation - EUH208
Environmental hazards	Not Classified
	Not Classified
Classification (67/548/EEC or 1999/45/EC)	
Classification (67/548/EEC or	
Classification (67/548/EEC or 1999/45/EC)	
Classification (67/548/EEC or 1999/45/EC) 2.2. Label elements	Not Classified EUH208 Contains Calcium long chain alkaryl sulphonate, Calcium long chain alkaryl
Classification (67/548/EEC or 1999/45/EC) 2.2. Label elements Hazard statements Supplemental label	Not Classified EUH208 Contains Calcium long chain alkaryl sulphonate, Calcium long chain alkaryl sulphonate. May produce an allergic reaction.

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients		
3.2. Mixtures		
Distillates, hydrotreated heav	y paraffinic	60-100%
CAS number: 64742-54-7	EC number: 265-157-1	REACH registration number: 01- 2119484627-25-0014
Classification Not Classified	Clas: -	sification (67/548/EEC or 1999/45/EC)
Distillates (petroleum) solven	t-dewaxed heavy paraffinic	10-30%
CAS number: 64742-65-0	EC number: 265-169-7	REACH registration number: 01- 2119471299-27-XXXX
A petroleum product. DMSO	extract < 3 % weight ( IP 346 )	
Classification Not Classified	Clas -	sification (67/548/EEC or 1999/45/EC)
Polyolefin polyamine succinir CAS number: —	nide polyol	1-5%
<b>Classification</b> Aquatic Chronic 4 - H413	Class R53.	sification (67/548/EEC or 1999/45/EC)
Propylene Pentamer CAS number: 15220-87-8		<1%
Classification Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		<b>sification (67/548/EEC or 1999/45/EC)</b> 65. Xi;R38. N;R51/53.
The Full Text for all R-Phrases	s and Hazard Statements are Displaye	d in Section 16.
Composition comments	registration, does not meet the minin	ot appear the substance is either exempt from num registration date has not yet come due or this
SECTION 4: First aid measure	es	
4.1. Description of first aid me	asures	
General information	Get medical attention if any discomfo	ort continues.
Inhalation		eed as follows. Move affected person to fresh air and comfortable for breathing. Get medical attention if any
Ingestion	Get medical attention if any discomfo	ort continues. Do not induce vomiting.
Skin contact	Remove contaminated clothing imme	ediately and wash skin with soap and water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rise for at least 15 minutes. Get medical attention promptly if symptoms cour after washing.   4.2. Most important symptoms and effects, both acute and delayed Immediately.   General information If aspiration into the lungs is suspected, eg when vomitting, admit to hospital immediately.   Inhelation Upper respiratory irritation.   Ingestion May cause disconfort if swallowed. The product contains mineral oil, which if aspirated into the lungs troug vomiting after ingestion, may result in chemical pneumonia.   Skin contact Prolonged contact may cause redness, irritation and dry skin.   Eye contact Irritation of eyes and mucous membranes.   4.3. Indication of any immediate stantion and special treatment needed Notes on the doctor   Notes on the doctor Treat symptomatically.   SECTION 5: Firefighting media Extinguish with foam, carbon dioxide, dry powder or water fog.   Unsultable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.   Unsultable extinguishing media Note some of which may be toxic.   5.3. Special hazards areing is furtiacance or mixture Special hazards areing and water ported in against nuisance dut must be used when the airborne concentration exceeds 10 mgm3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some			
General Information If aspiration into the lungs is suspected, eg when vomitting, admit to hospital immediately, Inhalaton   Upper respiratory irritation. May cause disconflort if swallowed. The product contains mineral oil, which if aspirated into the lungs through vomitting after ingestion, may result in chemical pneumonia.   Skin contact Prolonged contact may cause redness, irritation and dry skin.   Eye contact Irritation of eyes and mucous membranes.   4.3. Indication of any immediate medical attention and special treatment needed   Notes for the doctor Treat symptomatically.   SECTION 5: Firefighting mealae Extinguishing media   Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.   Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.   Specific hazards Heat from fire could result in drums bursting   Hazardous combustion Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of nitrogen. Fire may also create other uniderified organic gases some of which may be toxic.   5.3. Advice for firefighters Protection against nuisance dust must be used when the airborne some sets.   Special protective equipment and emergency procedures Personal proceutions, protective equipment and emergency procedures   Pactorin firefighters For personal protection, s	Eye contact	apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms	
Inhelation Upper respiratory irritation.   Ingestion May cause discomfort if swallowed. The product contains mineral oil, which if aspirated into the lungs through vomitting after ingestion, may result in chemical pneumonia.   Skin contact Prolonged contact may cause redness, irritation and dry skin.   Eye context Irritation of eyes and muccus membranes.   4.3. Indication of any immediate medical attention and special treatment needed   Notes for the doctor Treat symptomatically.   SECTION 5: Firefighting measures 5.1. Extinguishing media   Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.   Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.   Specific hazards Heat from fine could result in drums bursting   Hazards and might media Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   SJ. Advice for firefighters Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   SJ. Advice for firefighters Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of nitrogen. Fire may also create other unidentified organ	4.2. Most important symptoms	and effects, both acute and delayed	
IngestionMay cause discomfort if swallowed. The product contains mineral oil, which if aspirated into the lungs through vomitting after ingestion, may result in chemical pneumonia.Skin contactProlonged contact may cause redness, irritation and dry skin.Eye contactIrritation of eyes and mucous membranes.4.3. Indication of any immediate medical attention and special treatment neededNotes for the doctorTreat symptomatically.SECTION 5: Firefighting measures5.1. Extinguishing mediaSubable extinguishing mediaSubable extinguishing mediaSubable extinguishing media5.2. Special hazards arising from the substance or mixtureSpecific hazardsHeat from fire could result in drums burstingHazardous combustion productsProtection against nuisance dust must be used when the airborne concentration exceeds 10 mgm3. Oxides of arbor. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.5.3. Advice for firefightersProtective actions during torfietightersSpecial protective equipment torfietightersSection 11. Presonal precautions, protective squipment and emergency proceduresPersonal precautions surfaces.6.1. Personal precautions surfaces.Charton spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.6.3. Methods and material for containment and orearth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water contacting spilled material or leaking	General information	If aspiration into the lungs is suspected, eg when vomitting, admit to hospital immediately.	
the lungs through vomitting after ingestion, may result in chemical pneumonia.   Skin contact Prolonged contact may cause redness, irritation and dry skin.   Eye contact Irritation of eyes and mucous membranes.   4.3. Indication of any immediate medical attention and special treatment needed   Notes for the doctor Treat symptomatically.   SECTION 5: Firefighting media Suttable extinguishing media   Suttable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.   Unsuttable extinguishing media Do no use water jet as an extinguisher, as this will spread the fire.   secold hazards Heat from fire could result in drums bursting   Hazardous combustion products Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Control run-off water by containing and keeping it out of severs and watercourses.   SECTION 6: Accidental release For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.   6.1. Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.   6.2. Environmental precautions Cortain spillage with sand or earth. Avoid the spillage or runoff entering drains, severs or watercourses.	Inhalation	Upper respiratory irritation.	
Eye contact Irritation of eyes and mucous membranes.   4.3. Indication of any immediate medical attention and special treatment needed   Notes for the doctor Treat symptomatically.   SECTION 5: Firefighting measures 5.1. Extinguishing media   Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.   Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.   5.2. Special hazards arising from the substance or mixture Specific hazards   Paet from fire could result in drums bursting Hazardous combustion   products Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of arbor. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of arbor. Oxides of arbor. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Protective actions during Control run-off water by containing and keeping it out of sewers and watercourses.   Special protective equipment and emergency procedures Personal precautions. For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.   6.1. Personal precautions F	Ingestion		
4.3. Indication of any immediate medical attention and special treatment needed   Notes for the doctor Treat symptomatically.   SECTION 5: Firefighting media Extinguishing media   Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.   Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire.   media 5.2. Special hazards arising from the substance or mixture   Specific hazards Heat from fire could result in drums bursting   Hazardous combustion Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Control run-off water by containing and keeping it out of sewers and watercourses.   Protective equipment Wear self-contained breathing apparatus.   for firefighters For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.   6.1. Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.   6.2. E	Skin contact	Prolonged contact may cause redness, irritation and dry skin.	
Notes for the doctor Treat symptomatically.   SECTION 5: Firefighting meala   Suitable extinguishing media   Suitable extinguishing media   Suitable extinguishing media   Do not use water jet as an extinguisher, as this will spread the fire.   media   5.2. Special hazards arising from the substance or mixture   Specific hazards Heat from fire could result in drums bursting   Hazardous combustion products Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Control run-off water by containing and keeping it out of sewers and watercourses.   Protective equipment Wear self-contained breathing apparatus.   for firefighters For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.   6.1. Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.   6.2. Environmental precautions Contain spillage with sand or earth. Avoid the spillage or runoff enterin	Eye contact	Irritation of eyes and mucous membranes.	
Notes for the doctor Treat symptomatically.   SECTION 5: Firefighting meala   Suitable extinguishing media   Suitable extinguishing media   Suitable extinguishing media   Do not use water jet as an extinguisher, as this will spread the fire.   media   5.2. Special hazards arising from the substance or mixture   Specific hazards Heat from fire could result in drums bursting   Hazardous combustion products Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Control run-off water by containing and keeping it out of sewers and watercourses.   Protective equipment Wear self-contained breathing apparatus.   for firefighters For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.   6.1. Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.   6.2. Environmental precautions Contain spillage with sand or earth. Avoid the spillage or runoff enterin	4.3. Indication of any immedia	te medical attention and special treatment needed	
5.1. Extinguishing media   Sultable extinguishing media   Extinguishing media   Sultable extinguishing   Do not use water jet as an extinguisher, as this will spread the fire.   media   5.2. Special hazards arising from the substance or mixture   Specific hazards Heat from fire could result in drums bursting   Hazardous combustion Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Protective actions during   Protective actions during Control run-off water by containing and keeping it out of sewers and watercourses.   for firefighters SECTION 6: Accidental release measures   6.1. Personal precautions, protective equipment and emergency procedures   Personal precautions For personal protection, see Section 8. In case			
5.1. Extinguishing media   Sultable extinguishing media   Extinguishing media   Sultable extinguishing   Do not use water jet as an extinguisher, as this will spread the fire.   media   5.2. Special hazards arising from the substance or mixture   Specific hazards Heat from fire could result in drums bursting   Hazardous combustion Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Protective actions during   Protective actions during Control run-off water by containing and keeping it out of sewers and watercourses.   for firefighters SECTION 6: Accidental release measures   6.1. Personal precautions, protective equipment and emergency procedures   Personal precautions For personal protection, see Section 8. In case	SECTION 5: Firefighting meas	sures	
Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.   Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.   section Do not use water jet as an extinguisher, as this will spread the fire.   Specific hazards Heat from fire could result in drums bursting   Hazardous combustion products Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Protective actions during freefighting   Protective actions during freefighting Control run-off water by containing and keeping it out of sewers and watercourses.   SECTION 6: Accidental release measures Section 10 freefighters   Section al precautions, protective equipment and emergency procedures Presonal precautions   Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.   6.2. Environmental precautions Contain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in wate			
Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.   5.2. Special hazards arising from the substance or mixture   Specific hazards Heat from fire could result in drums bursting   Hazardous combustion products Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Control run-off water by containing and keeping it out of sewers and watercourses.   Frefighting Control run-off water by containing apparatus.   Special protective equipment tor firefighters Wear self-contained breathing apparatus.   6.1. Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.   6.2. Environmental precautions Contain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.   6.3. Methods and material for containment and cleaning up Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers. Spillages or uncontrolled discharges into watercourses		Extinguish with foam, carbon dioxide, dry powder or water fog.	
media5.2. Special hazards arising from the substance or mixtureSpecific hazardsHeat from fire could result in drums burstingHazardous combustion productsProtection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.5.3. Advice for firefightersProtection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.5.3. Advice for firefightersControl run-off water by containing and keeping it out of sewers and watercourses.Special protective equipment for firefightersWear self-contained breathing apparatus.Special protective equipment tor firefightersWear self-contained breathing apparatus.SECTION 6: Accidental release measures6.1. Personal precautions, protective equipment and emergency proceduresPersonal precautionsFor personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.6.2. Environmental precautionsContain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.6.3. Methods and material for containment and cleaning up Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or un			
Specific hazards Heat from fire could result in drums bursting   Hazardous combustion products Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.   5.3. Advice for firefighters Control run-off water by containing and keeping it out of sewers and watercourses.   Special protective equipment for firefighters Control run-off water by containing apparatus.   SECTION 6: Accidental release measures Environmental precautions, protective equipment and emergency procedures   Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.   6.2. Environmental precautions Contain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.   6.3. Methods and material for containment and cleaning up Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate requipment			
Hazardous combustion productsProtection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.5.3. Advice for firefightersFortective actions during firefightingControl run-off water by containing and keeping it out of sewers and watercourses.5.7. Special protective equipment for firefightersWear self-contained breathing apparatus. for firefightersSECTION 6: Accidental release measures6.1. Personal precautions, protective equipment and emergency proceduresPersonal precautionsFor personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.6.2. Environmental precautionsContain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.6.3. Methods and material for containment and cleaning up Methods for cleaning upContain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment	5.2. Special hazards arising from the substance or mixture		
productsmg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.5.3. Advice for firefightersControl run-off water by containing and keeping it out of sewers and watercourses.Protective actions during firefightingControl run-off water by containing and keeping it out of sewers and watercourses.Special protective equipment for firefightersWear self-contained breathing apparatus.SECTION 6: Accidental release measures6.1. Personal precautions, protective equipment and emergency proceduresPersonal precautionsFor personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.6.2. Environmental precautionsContain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.6.3. Methods and material for containment and cleaning upMethods for cleaning upContain spillage with sand or earth. Collect spillage for reclarmation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment	Specific hazards	Heat from fire could result in drums bursting	
Protective actions during frefightingControl run-off water by containing and keeping it out of sewers and watercourses.Special protective equipment for firefightersWear self-contained breathing apparatus. for firefightersSECTION 6: Accidental release measures6.1. Personal precautions, protective equipment and emergency proceduresPersonal precautionsFor personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.6.2. Environmental precautionsContain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.6.3. Methods and material for containment and cleaning upContain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment		mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic	
firefighting Special protective equipment Wear self-contained breathing apparatus.   for firefighters SECTION 6: Accidental release measures   6.1. Personal precautions, protective equipment and emergency procedures   Personal precautions For personal protective, see Section 8. In case of spills, beware of slippery floors and surfaces.   6.2. Environmental precautions Contain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.   6.3. Methods and material for containment and cleaning up Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment	5.3. Advice for firefighters		
for firefighters   SECTION 6: Accidental release measures   6.1. Personal precautions, protective equipment and emergency procedures   Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.   6.2. Environmental precautions Environmental precautions   Contain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.   6.3. Methods and material for containment and cleaning up   Methods for cleaning up Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment	-	Control run-off water by containing and keeping it out of sewers and watercourses.	
6.1. Personal precautions, protective equipment and emergency procedures   Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.   6.2. Environmental precautions Environmental precautions   Contain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.   6.3. Methods and material for containment and cleaning up   Methods for cleaning up Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment		Wear self-contained breathing apparatus.	
Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.   6.2. Environmental precautions Environmental precautions   Contain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.   6.3. Methods and material for containment and cleaning up   Methods for cleaning up   Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment	SECTION 6: Accidental releas	e measures	
surfaces.   6.2. Environmental precautions   Environmental precautions   Contain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.   6.3. Methods and material for containment and cleaning up   Methods for cleaning up Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment	6.1. Personal precautions, pro	tective equipment and emergency procedures	
Environmental precautionsContain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.6.3. Methods and material for containment and cleaning upMethods for cleaning upMethods for cleaning upContain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment	Personal precautions		
watercourses. The product is insoluble in water and will spread on the water surface.6.3. Methods and material for containment and cleaning upMethods for cleaning upContain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment	6.2. Environmental precaution	8	
Methods for cleaning up Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment	Environmental precautions		
containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment	6.3. Methods and material for	containment and cleaning up	
	Methods for cleaning up 6.4. Reference to other section	containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment	

### 6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.	
SECTION 7: Handling and sto	rage	
7.1. Precautions for safe hand	ling	
Usage precautions	Avoid spilling. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.	
7.2. Conditions for safe storage, including any incompatibilities		
Storage precautions	Store in tightly-closed, original container in a dry, cool and well-ventilated place.	
Storage class	Miscellaneous hazardous material storage.	
7.3. Specific end use(s)		
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.	
SECTION 8: Exposure Controls/personal protection		
8.1. Control parameters		

#### Occupational exposure limits

#### Distillates, hydrotreated heavy paraffinic

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m<sup>3</sup> Short-term exposure limit (15-minute): ACGIH 10 mg/m<sup>3</sup>

#### Distillates (petroleum) solvent-dewaxed heavy paraffinic

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m<sup>3</sup> Short-term exposure limit (15-minute): ACGIH 10 mg/m<sup>3</sup>

#### **Propylene Pentamer**

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup>

ACGIH = American Conference of Governmental Industrial Hygienists.

WEL = Workplace Exposure Limit

#### 8.2. Exposure controls

#### Protective equipment



Appropriate engineering controls	Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.
Hand protection	The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
Other skin and body protection	Use barrier creams to prevent skin contact.
Hygiene measures	Use engineering controls to reduce air contamination to permissible exposure level. Wash promptly with soap and water if skin becomes contaminated.

Respiratory protection	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.
Thermal hazards	Not anticipated under normal conditions of use. The product is combustible if heated excessively and an ignition source is applied.
Environmental exposure controls	Do not allow product to contaminate land.

## **SECTION 9: Physical and Chemical Properties**

9.1. Information on basic physic	ical and chemical properties
Appearance	Liquid.
Colour	Amber.
Odour	Characteristic. Oil-like.
Odour threshold	Not known.
рН	Not applicable.
Melting point	-25°C Pour point
Initial boiling point and range	>320°C @ 101.3 kPa
Flash point	219°C PMCC (Pensky-Martens closed cup).
Evaporation rate	Not relevant.
Upper/lower flammability or explosive limits	Not known.
Other flammability	Product is not flammable but on excessive heating may become combustible.
Vapour pressure	<0.1 kPa @ 20°C
Vapour density	Not determined.
Relative density	0.879 @ 15.6°C
Solubility(ies)	Insoluble in water. Soluble in the following materials: Organic solvents.
Partition coefficient	Not determined. log Kow: > 7 The above figure is typical of mineral oil.
Auto-ignition temperature	No specific test data are available.
Decomposition Temperature	Not determined.
Viscosity	89.6 cSt @ 40°C
Explosive properties	Not considered to be explosive.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.
9.2. Other information	
Volatile organic compound	The product is a complex mixture, the majority of which would not be classed as a VOC. However it cannot be discounted that trace or low levels of VOC's may be present.
SECTION 10: Stability and rea	oth/h/

SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
10.2. Chemical stability	
Stability	Stable at normal ambient temperatures and when used as recommended.
10.3. Possibility of hazardous	
Possibility of hazardous	Unlikely to occur under normal conditions of use. Unlikely to occur.
reactions	
10.4. Conditions to avoid	
Conditions to avoid	Avoid heat, flames and other sources of ignition.
10.5. Incompatible materials	
Materials to avoid	Strong oxidising agents.
10.6. Hazardous decomposition	on products
Hazardous decomposition	Oxides of carbon. Oxides of nitrogen.
products	
SECTION 11: Toxicological in	
11.1. Information on toxicolog	ical effects
Acute toxicity - oral	
Notes (oral LD₅o)	Not expected to be highly toxic based on information of ingredients. Based on available data the classification criteria are not met.
Acute toxicity - dermal	
Notes (dermal LD₅₀)	Not expected to be highly toxic based on information of ingredients. Based on available data the classification criteria are not met.
Acute toxicity - inhalation	
Notes (inhalation $LC_{50}$ )	Not determined. The product is unlikely to present any significant inhalation hazard at ambient temperatures and under normal conditions of use.
Serious eye damage/irritation	
Serious eye damage/irritation	May cause mild, short lasting discomfort to eyes.
Respiratory sensitisation	
Respiratory sensitisation	No evidence to suggest the product will be a respiratory sensitiser. Repeated exposure to oil mists may cause respiratory damage.
Skin sensitisation	
Skin sensitisation	Not expected to be a skin sensitizer based on information on components.
Carcinogenicity	
Carcinogenicity	This product contains mineral oils which are considered to be severly refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP346 test
Reproductive toxicity	
Reproductive toxicity - fertility	No data available to suggest the product will cause reproductive toxicity.
Specific target organ toxicity -	single exposure
STOT - single exposure	Based on available data the classification criteria are not met.
Specific target organ toxicity - repeated exposure	
STOT - repeated exposure	Based on available data the classification criteria are not met.

Aspiration hazard Aspiration hazard	Kinematic viscosity > 20.5 mm <sup>2</sup> /s. The product viscosity is greater than the upper limit assigned for classification. The product contains mineral oil. If aspirated into the lungs e.g. through vomitting after ingestion admit to hospital immediately.
General information	This product has low toxicity. Only large quantities are likely to have adverse effects on human health.
Inhalation	Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature.
Ingestion	No harmful effects expected from quantities likely to be ingested by accident.
Skin contact	Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking.
Eye contact	May cause temporary eye irritation.
Acute and chronic health hazards	Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer.

SECTION 12: Ecological Info	rmation
Ecotoxicity	Based on available data the classification criteria are not met. Not regarded as dangerous for the environment.
12.1. Toxicity	
Toxicity	Based on available data the classification criteria are not met. Not considered toxic to fish.
Acute toxicity - aquatic invertebrates	Based on available data the classification criteria are not met.
12.2. Persistence and degrad	ability
Persistence and degradability	The product contains mineral oil which has limited biodegradability in CEC test methods but will biodegrade slowly in aerobic water and sediments and is considered ultimately biodegradable.
Stability (hydrolysis)	The product is based on highly refined mineral oils that are considered stable to hydrolysis.
Biodegradation	The product is not considered readily biodegradeable, albeit the major constituents are expected to ultimately biodegrade.
Biological oxygen demand	Not determined.
Chemical oxygen demand	Not determined.
12.3. Bioaccumulative potenti	al
Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.
Partition coefficient	Not determined. log Kow: > 7 The above figure is typical of mineral oil.
12.4. Mobility in soil	
Mobility	The product is non-volatile. The product is insoluble in water and will spread on the water surface.
Henry's law constant	Not determined.
12.5. Results of PBT and vPv	Bassessment
Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.
12.6. Other adverse effects	
Other adverse effects	None known.
SECTION 13: Disposal considerations	
13.1. Waste treatment method	ds
General information	This material and its container must be disposed of as hazardous waste. Dispose of waste via a licensed waste disposal contractor.
Disposal methods	Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Dispose of waste via a licensed waste disposal contractor.
Waste class	European waste catalogue (EWC) number = 13 02 08*
SECTION 14: Transport inform	nation
General	The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

#### 14.1. UN number

Not applicable.

### 14.2. UN proper shipping name

Not applicable.

#### 14.3. Transport hazard class(es)

No transport warning sign required.

#### 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

#### Environmentally hazardous substance/marine pollutant

### 14.6. Special precautions for user

Not applicable.

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

### Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

#### SECTION 15: Regulatory information

15.1. Safety, health and e	environmental regulations/legislation specific for the substance or mixture
National regulations	Health and Safety at Work etc. Act 1974 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). Control of Substances Hazardous to Health Regulations 2002 (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].
EU legislation	Dangerous Preparations Directive 1999/45/EC. Dangerous Substances Directive 67/548/EEC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40. Safety Data Sheets for Substances and Preparations.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### Inventories

#### Canada - DSL/NDSL

All the ingredients are listed or exempt.

### US - TSCA

All the ingredients are listed or exempt.

#### Australia - AICS

All the ingredients are listed or exempt.

#### Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

#### Philippines – PICCS All the ingredients are listed or exempt.

#### New Zealand - NZIOC

All the ingredients are listed or exempt.

#### SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	05/11/2015
Revision	1
SDS number	21570
Hazard statements in full	EUH208 Contains Calcium long chain alkaryl sulphonate, Calcium long chain alkaryl sulphonate. May produce an allergic reaction. H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.