

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Trade name : SEAL LUBRICANT
Product code : 30030-MBC
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Intended for general public
Main use category : Consumer use
Use of the substance/mixture : Lubricant
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Thetford BV
Nijverheidsweg 29
P.O. Box 169
4879 AP Etten-Leur - The Netherlands
T +31(0)765042200 - F +31(0)765042300
ChemSupport@thetford.eu - www.thetford-europe.com
E-mail address of competent person responsible for the SDS :
sds@thetford.eu

1.4. Emergency telephone number

Emergency number : Thetford B.V. : +31 (0)76 5042200 (Reachable during office hours)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Aerosol, Category 1 H222;H229
Flammable liquids, Category 1 H224
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Extremely flammable liquid and vapour.

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

Signal word (CLP) : Danger
Hazard statements (CLP) : H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P260 - Do not breathe dusts or mists.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
UFI : 3JT8-EN3D-480T-KJNK

SEAL LUBRICANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Child-resistant fastening : Not applicable

Tactile warning : Applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
pentane	(CAS-No.) 109-66-0 (EC-No.) 203-692-4 (EC Index-No.) 601-006-00-1	1 - 2,5	Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Generally the product does not irritate the skin. Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse with opened eye for several minutes under running water. In case irritation persists, consult a doctor. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Shortness of breath.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Carbon dioxide. Foam.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol. Extremely flammable liquid and vapour.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment. DO NOT fight fire when fire reaches explosives. Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. No open flames, no sparks, and no smoking.

SEAL LUBRICANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Store away from other materials. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Hazardous waste due to potential risk of explosion. Do not pierce or burn, even after use.
Precautions for safe handling	: Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Do not spray on an open flame or other ignition source. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.
Storage conditions	: Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Store in a cool location. Observe official regulations on storing packagings with pressurized containers. Store in a well-ventilated place. Keep cool. Keep container tightly closed.
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

Lubricant.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses. Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SEAL LUBRICANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: -0,5 °C
Flash point	: -60 °C
Auto-ignition temperature	: 365 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: 2100 hPa 20 °C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0,6 g/cm ³
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Product is not explosive. Without adequate ventilation formation of explosive mixtures may be possible.
Oxidising properties	: No data available
Explosive limits	: 1,4 - 8,5 vol %

9.2. Other information

VOC content : 90 % 541,8 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable liquid and vapour.

10.2. Chemical stability

Not established. Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating. Avoid contact with hot surfaces. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified

SEAL LUBRICANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Additional information	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met

SEAL LUBRICANT

Vaporizer	Aerosol
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

pentane (109-66-0)

LC50 fish 1	4,26 mg/l Oncorhynchus mykiss
LC50 other aquatic organisms 1	10,7 mg/l Pseudokirchneriella subcapitata
EC50 Daphnia 1	2,7 mg/l Daphnia magna
NOEC (acute)	7,51 mg/l Pseudokirchneriella subcapitata

12.2. Persistence and degradability

SEAL LUBRICANT

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

SEAL LUBRICANT

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information	: Avoid release to the environment.
------------------------	-------------------------------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.
Additional information	: Flammable vapours may accumulate in the container.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information



In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1950	UN 1950	UN 1950	Not applicable	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	AEROSOLS, flammable	Not applicable	Not applicable

SEAL LUBRICANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2	UN 1950 AEROSOLS, flammable, 2	Not applicable	UN 1950 , 2.1
14.3. Transport hazard class(es)				
2.1	2	2	Not applicable	2.1
	Not applicable	Not applicable	Not applicable	
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F
Special provisions (ADR) : 190, 327, 344, 625
Limited quantities (ADR) : 1I
Excepted quantities (ADR) : E0
Transport category (ADR) : 2
Tunnel restriction code (ADR) : D

Transport by sea

No data available

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances
Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.
Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.

VOC content : 90 % 541,8 g/l

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out
A chemical safety assessment has been carried out

SEAL LUBRICANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Indication of changes:

Section	Changed item	Change	Comments
	Vaporizer	Added	
	Date of issue	Modified	
	Revision date	Modified	
	Supersedes	Modified	
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified	
2.2	Precautionary statements (CLP)	Modified	

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H222	Extremely flammable aerosol.
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.